

## HPSIL® 520A Friction-type Precipitated silica

### Characteristics

HPSIL® 520A friction-type is a kind of high purity white fluffy powder, widely used in toothpaste.

### Packaging and storage

HPSIL® 520A friction-type is supplied in 10kg kraft paper bags. We recommend to store the product in closed containers under dry conditions and to protect the material from volatile substances.

### Applications

- Toothpaste

### Properties

- Improve friction in toothpaste
- Good dissolvability with fluoride and other

### Characteristic physico-chemical data

Properties and test methods	Unit	Typical Value
Silica content (based on ignited material)	%	≥95
Appearance		White powder
Whiteness	%	≥93
pH value (in 5% dispersion)		6.5-8.5
Pass 320 mesh screen	%	≥ 98
Loss on drying (105°C)	%	≤10
Loss on ignition (900°C)	%	≤ 8.3
Water absorption value	ml/20g	17-20
Na <sub>2</sub> SO <sub>4</sub> content	%	≤ 0.4
NaCl content	%	≤ 0.1
Sulfide content		None
Heavy metals (Pb) content	mg/kg	≤20
As content	mg/kg	≤2
Bacilli	cfu/g	≤200

### Contact information

**HENAN MINMETALS EAST INDUSTRIAL Co., Ltd.**  
**Address** RENMIN ROAD, JIAOZUO CITY,  
HENAN PROVINCE, 454000  
CHINA

**Tel** +86 391 3565627  
**Fax** +86 391 3565657  
**Email** info@minmetalseast.com  
**Internet** www.minmetalseast.com

The data presented in this document is based on our best knowledge. We disclaim any warranty and liability whatsoever as to accuracy and completeness of such information as well as to the potential infringement of any proprietary rights. We reserve the right to alter product constants within the scope of technical progress or new developments. Any user of our products shall bear the full risk connected to their use including but not limited to their properties and fitness for any purpose.